

GB4C, Mechanical Grounding Connector, Cable to Bar

By Burndy Catalog # GB4C



Mechanical Grounding Connector, Cable to 1/4" Thick Bar, 8 AWG (Sol)- 4 AWG (Str), 3/8" Stud1-1/4 IN Width.

Application

For Copper Cable To Bar, Direct Burial Cable

General

| EU RoHS Indicator | Yes |
|--|------------------------|
| Installation Torque Recommended in-lb | 240 lb-in |
| | |
| Material | Copper Alloy |
| Material Type - Screw | DURIUM™ Silicon Bronze |
| Physical Attribute - Screw | Hexagonal Bolt |
| Туре | |
| Plated | Ν |
| Plating Type | Unplated |
| Sub Brand | MECHANICAL CONNECTOR |
| Туре | GB |
| UPC | 781810231180 |
| UPC 12 Digit | 7818102311800 |
| Dimensions | |

Dimensions

| Dimension - Height inch | 1.49 in |
|--|-----------|
| Dimension - L Length Overall | 22 mm |
| mm Dimension - Length Overall inch | 0.88 in |
| Dimension - Width fraction | 1-3/50 in |
| Dimension - Width inch | 1.06 in |

Conductor Related

| Conductor - Copper Solid Size | 8 AWG;7 AWG;6 AWG;5 AWG;4 AWG | |
|--|----------------------------------|--|
| Conductor - Copper Solid Size Range | 8 AWG-4 AWG | |
| Conductor - Copper Str Size | 8 AWG;7 AWG;6 AWG;5 AWG;4 AWG | |
| Conductor - Copper Str Size Range | 8 AWG-4 AWG | |
| Certifications and Compliance | | |
| Certification - CSA Approved | No | |
| Certification - UL Listed Direct Burial | Yes | |
| Industry Standard(s) | UL467 | |
| Standards - Industry Standards Met | UL467 | |
| Standards - RoHS Compliance Status | EX | |
| UL Listed | Yes | |

1

Logistics

Minimum Pack Quantity

Product Assets

3D Models - GB4C_MODEL-PDF 3D Models - GB4C_MODEL-IGES 3D Models - GB4C_MODEL-STEP Catalogs - Full Line BURNDY Catalog Customer Notices - Prop 65 Notice Sales Drawings - sc091657-01